

## VERIFICATION OF COMPLIANCE

| No.:                 | GZES2007022912PV01  |
|----------------------|---|
| Applicant:           | Shenzhen SOFAR SOLAR Co., Ltd.<br>401, Building 4, AnTongDa Industrial Park, District 68, XingDong<br>Community, XinAn Street, BaoAn District, Shenzhen City,<br>Guangdong Province, P.R. China |
| Manufacturer:        | Shenzhen SOFAR SOLAR Co., Ltd.<br>401, Building 4, AnTongDa Industrial Park, District 68, XingDong<br>Community, XinAn Street, BaoAn District, Shenzhen City,<br>Guangdong Province, P.R. China |
| Product Name:        | Hybrid Inverter (Three Phase)   |
| Product Description: | Inverter used in PV system  |
| Model No.:           | HYD 5KTL-3PH, HYD 6KTL-3PH;<br>HYD 8KTL-3PH, HYD 10KTL-3PH;   |

| Trade Mark:                        |                           |
|------------------------------------|---------------------------|
| Rating:                            | Refer to page 2 to page 3 |
| Intended Use:                      | PV System                 |
| Protection against Electric Shock: | Class I                   |
| Additional Information (if any):   | IP 65                     |
|                                    | Firmware version: V2.00   |

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard:Engineering Recommendation G98 Issue 1 - Amendment 3 March<br/>2019as shown in theTest Report Number(s):GZES200702291201

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

David Guo

Senior Technical Manager SGS-CSTC 2020-08-27

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)



No.:

## GZES2007022912PV01

Other information added : Ratings

| Model                                    | HYD<br>5KTL-3PH | HYD<br>6KTL-3PH     | HYD<br>8KTL-3PH | HYD<br>10KTL-3PH |
|--|-----------------|---------------------|-----------------|------------------|
|  |                 | PV String Input Dat |                 |                  |
| Max. DC voltage                          | 1000∨           |                     |                 |                  |
| MPPT voltage range                       | 180V~960V       |                     |                 |                  |
| Full power MPPT voltage range            | 250V~850V       | 320V~850V           | 360V~850V       | 220V~850V        |
| Max. input current                       | 12.5A/12.5A     | 12.5A/12.5A         | 12.5A/12.5A     | 25A/25A          |
| Max. short current                       | 15A/15A         | 15A/15A             | 15A/15A         | 30A/30A          |
| Battery Input Data                       |                 |                     |                 |                  |
| Battery voltage<br>range                 | 180V~800V       |                     |                 |                  |
| Battery voltage range for full load      | 200V~800V       | 240V~800V           | 320V~800V       | 200V~800V        |
| No. of battery input                     | 1               |                     |                 | 2                |
| Nominal<br>charging/discharging<br>power | 5000W           | 6000W               | 8000W           | 10000W           |
| Max.<br>charging/discharging<br>current  | 25A             | 25A                 | 25A             | 50A<br>(25A/25A) |
| AC Output Data (On-g                     | ırid)           |                     |                 |                  |
| Nominal AC power                         | 5000W           | 6000W               | 8000W           | 10000W           |
| Max. AC power output to utility grid     | 5500VA          | 6600VA              | 8800VA          | 11000VA          |
| Max. AC power from utility grid          | 10000VA         | 12000VA             | 16000VA         | 20000VA          |
| Max. AC current output to utility groces | 8A              | 10A                 | 13A             | 16A              |
| Rated AC current output to utility grid  | Z ZA            | 8.7A                | 11.6A           | 14.5A            |
| Max-AC ourrent                           | THE REAL        | 17A                 | 24A             | 29A              |

David Guo

Senior Technical Manager SGS-CSTC

\*

2020-08-27

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.



No.:

## GZES2007022912PV01

| Nominal output voltage         | 3/N/PE, 230Vac                 |           |           |          |  |
|--------------------------------|--------------------------------|-----------|-----------|----------|--|
| Nominal output<br>freqency     | 50Hz                           |           |           |          |  |
| Output power factor            | ~1(0.8 leading to 0.8 lagging) |           |           |          |  |
| AC Output Data (Ba             | ck-up)                         |           |           |          |  |
| Nominal<br>output power        | 5000W                          | 6000W     | 8000W     | 10000W   |  |
| Max. output power              | 5500VA                         | 6600VA    | 8800VA    | 11000VA  |  |
| Rated. output current          | 7.2A                           | 8.7A      | 11.6A     | 14.5A    |  |
| Max. output<br>current         | 8A                             | 10A       | 13A       | 16A      |  |
| Peak output current, Duration  | 15A, 60s                       | 18A, 60s  | 24A, 60s  | 30A, 60s |  |
| Nominal output voltage         | 3/N/PE, 230Vac                 |           |           |          |  |
| Nominal output<br>freqency     | 50Hz                           |           |           |          |  |
| Output power factor            | ~1(0.8 leading to 0.8 lagging) |           |           |          |  |
| Operating<br>temperature range | -30°C ~60°C                    |           |           |          |  |
| Ingress protection             | IP65                           |           |           |          |  |
| Protective class               | Class I                        |           |           |          |  |
| Cooling method                 | Heat sink                      | Heat sink | Heat sink | Fan      |  |



Senior Technical Manager SGS-CSTC

2020-08-27

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)