

## **VERIFICATION OF COMPLIANCE**

No.:	GZES2007022912PV02A01
Applicant:	Shenzhen SOFAR SOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen SOFAR SOLAR Co., Ltd. 401, Building 4, AnTongDa Industrial Park, District 68, XingDong Community, XinAn Street, BaoAn District, Shenzhen, Guangdong, China
Product Name:	Hybrid Inverter (Three Phase)
Product Description:	Inverter used in PV system
Model No.:	HYD 5KTL-3PH, HYD 6KTL-3PH, HYD 8KTL-3PH HYD 10KTL-3PH, HYD 15KTL-3PH, HYD 20KTL-3PH
Trade Mark:	SEFAR
Rating.	Refer to page 2 to page 3

	SULAR
Rating:	Refer to page 2 to page 3
Intended Use:	PV System
Protection against Electric Shock:	Class I
Additional Information (if any):	IP 65
	Firmware version: V2.00

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard:ENA Engineering Recommendation G99 Issue 1 Amendment 6<br/>09 March 2020as shown in theGZES200702291202

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SCS CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards.

David Gud Senior Technical Manage

SGS-CSTC

2021-07-21

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)



No.:

## GZES2007022912PV02A01

Other information added : Ratings

Model	HYD 5KTL-3PH	HYD 6KTL-3PH			HYD 15KTL-3PH	HYD 20KTL-3PH			
	SITE-SI II		ng Input Data			ZUITE-UIT			
Max. DC voltage	1000V								
MPPT voltage range	180V~960V								
Full power MPPT voltage range	250V~850V	320V~850V	360V~850V	220V~850V	450V~850V				
Max. input current	12.5A/12.5A	12.5A/12.5A	12.5A/12.5A	25A/25A	25A/25A	25A/25A			
Max. short current	15A/15A	15A/15A	15A/15A	30A/30A	30A/30A	30A/30A			
Battery Input Data Battery voltage range	180V~800V								
Battery voltage range for full load	200V~800V	240V~800V	320V~800V	200V~800V	300V~800V	400V~800V			
No. of battery input		1		2					
Nominal charging/discharging power	5000W	6000W	8000W 10000W		15000W	20000W			
Max. charging/discharging current	25A	25A	25A	50A (25A/25A)	50A (25A/25A)	50A (25A/25A)			
AC Output Data (On-g	rid)		I			I			
Nominal AC power	5000W	6000W	8000W	10000W	15000W	20000W			
Max. AC power output to utility grid	5500VA	6600VA	8800VA	300VA 11000VA 16500		22000VA			
Max. AC power from utility grid	10000VA	12000VA	16000VA	20000VA	30000VA	40000VA			
Max. AC current output to utility grid	8A	10A	13A	16A	24A	32A			
Rated AC current output to utility grid	有風 72	8.7A	11.6A	14.5A	21.7A	29A			

David Guo Senior Technical Manager SGS-CSTC

(

2021-07-21

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.



No.:

## GZES2007022912PV02A01

Max. AC Current from utility grid	15A	17	'A	24	A	29/	Ą	44A		58A
Nominal output voltage	3/N/PE, 230Vac									
Nominal output freqency	50Hz									
Output power factor	~1(0.8 leading to 0.8 lagging)									
AC Output Data (Bad	AC Output Data (Back-up)									
Nominal output power	5000W	600	0W	8000	w	1000	0W	1500	0W	20000W
Max. output power	5500VA	6600	OVA	8800	VA	11000VA		16500VA		22000VA
Rated. output current	7.2A	8.7	7A	11.6	6A	14.5A		21.7A		29A
Max. output current	8A	10	A	13	A	16A		24A		32A
Nominal output voltage	3/N/PE, 230Vac									
Nominal output freqency	50Hz									
Output power factor	~1(0.8 leading to 0.8 lagging)									
Operating temperature range	-30°C ~60°C									
Ingress protection	IP65									
Protective class	Class I									
Cooling method	Heat sin	k	Heat sink		Heat	sink	Fan		Fan	Fan



2021-07-21

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)